

3G Cellular Gateway



Features

- Single analogue port
- Single SIM Card – Compatible with all Australian Carriers
- 3G Network Voice and Data
- LED Function Lights
- USB Data connection – use gateway as data modem for high speed 3G data access

Technical Parameters

- Multimode Operation – HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM
- Triple Band HSPA/UMTS 850/1900/2100 MHz
- Quad-band EDGE/GPRS/GSM 850/900/1800/1900 MHz
- HSUPA uplink up to 2.0 Mbps
- HSDPA downlink up to 7.2 Mbps
- WCDMA (UMTS) uplink data rate up to 384 kbps
- EDGE data up to 237 Kbps DL and 118 Kbps UL, 3GPP Release 4, class 12
- GPRS data up to 85.6 Kbps DL and 42.8 Kbps UL
- Reversal on Answer
- Power Supply: 12 Vdc
- Output Power:
 - Class 3 for UMTS/HSDPA/HSUPA
 - Class 4 for GSM 900
 - Class 1 for GSM 1800
 - Class E2 for EDGE 900/1800
- USB: USB 2.0 Full Speed
- Antenna Gain >1.5dBm
- Environmental
 - Operating Temperature: -10 ~ +55 C
 - Storage Temperature: -40 ~ +80 C
- RJ-11 phone interface: Dialing tone frequency 450Hz

On hook voltage	45v
Off hook current	30mA/41mA

Package Information

Size:	173(L) x 128(W) x 29(H)mm
Weight	282g